



| Specifications                                 |                    |
|------------------------------------------------|--------------------|
| Operating Weight (kg)                          | 8600               |
| Engine Power (kW/rpm)                          | 57.7/2200          |
| Standard Bucket Capacity (m <sup>3</sup> )     | 0.35               |
| Standard Bucket Volume Range (m <sup>3</sup> ) | 0.11-0.42          |
| Performance                                    |                    |
| Travel Speed (Low/High) (km/h)                 | 2.8/4.5            |
| Swing Speed (rpm)                              | 11.69              |
| Ground Pressure (kPa)                          | 37                 |
| Gradeability (o)                               | 35                 |
| Maximum Arm Crowd Fore (kN)                    | 38                 |
| Maximum Bucket Digging Force (kN)              | 56                 |
| Equipments                                     |                    |
| Engine Model                                   | Yanmar 4TNV98T-SFN |
| Displacement (L)                               | 3.319              |

Shanghai Longji Construction Machinery Co., Ltd.

**Add:** Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

**Post Code:** 201100

**E-mail:** [info@shlongji.com](mailto:info@shlongji.com)

**Tel:** +86-21-541-71571

**Fax:** +86-21-541-71572

**Website:** [www.shlongji.com](http://www.shlongji.com) Wheel Loader, Road Roller, Dump Truck

|                                            |                      |
|--------------------------------------------|----------------------|
| Swing Device Driving Type Hydraulic Drive  |                      |
| Travel Device Driving Type Hydraulic Drive |                      |
| Brake Type                                 | Hydraulic Lock       |
| Standard Track Shoe Type                   | Triple Grouser Shoes |
| Track Adjustment Device                    | Grease Tension       |
| Hydraulic Pump Type                        | Variable Piston Pump |
| Maximum Setting Pressure Traveling (MPa)   | 28.5                 |
| Working (MPa)                              | 28.5                 |
| <b>Implement</b>                           |                      |
| Boom Length (mm)                           | 3720                 |
| Arm Length (mm)                            | 1665                 |
| Bucket Radius (mm)                         | R1008                |
| <b>Refill Capacity</b>                     |                      |
| Fuel (diesel) (L)                          | 146                  |
| Hydraulic oil (Refilling) (L)              | 120                  |
| Battery Capacity                           | 85AH                 |

Shanghai Longji Construction Machinery Co., Ltd.

**Add:** Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

**Post Code:** 201100

**E-mail:** [info@shlongji.com](mailto:info@shlongji.com)

**Tel:** +86-21-541-71571

**Fax:** +86-21-541-71572

**Website:** [www.shlongji.com](http://www.shlongji.com) Wheel Loader,Road Roller,Dump Truck