



Principal dimension	
Operating Weight(kg)	1030
Standard Bucket Capacity (m ³)	0.02
Size of blade(mm)	930×183
Overall Length (trans pos)(mm)	2800
Overall Width (trans pos) (mm)	930
Overall Height (trans pos) (mm)	2300
Wheel Base(mm)	895
Length Of Track(mm)	1242
Width Of Track(mm)	180(rubber)
Clearnce under Counterweight (mm)	421.5
Ground Clearance (mm)	164
Tail Turning Radius(mm)	580
Operating envelope	
Maximum Digging Height(mm)	2737
Maximum Digging Depth(mm)	1415
Maximum Dumping Height(mm)	1951

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Website: www.shlongji.com Wheel Loader,Road Roller,Dump Truck

Maximum Vertical Digging Dist.(mm)	956
Minimum Turning Radius(mm)	1248
Maximum Digging Dist.(mm)	2831
Maximum Ground Digging Dist.(mm)	2727
Engine	
Engine Model	Yanmar 2TNV70
Rated Power(kw/rpm)	7.5/2400
Max. torque(N.m/rpm)	31.6~34.4/1800±100
Displacement(L)	0.57
hydraulic system	
Main pump rated flow(L/min)	22.5
Main pump rated speed(rpm)	2500
Working device circuit(Mpa)	16
Travel Circuit(Mpa)	16
Swing Circuit (Mpa)	9
Characteristic	
Maximum Gradeability(°)	30
Travelling Speed(km/h)	1.6-2.6
Swing speed(rpm)	7~9
Ground Pressure(Kpa)	≤27
Maximum traction(KN)	7.6/7.8
Bucket digging force (KN)	9.2
Arm digging force(KN)	4.8

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Website: www.shlongji.com Wheel Loader,Road Roller,Dump Truck