



Model		ZZ5256GJBM3246C (8290)	ZZ5257GJBM3247C (8290)
		HDT5257GJB (8336)	ZZ5257GJBN3247C (8336)
Whole Vehicle Performance & Parameters	Chassis	STEYR KING	HOWO
	Curb Weight (Kg)	12600	13500
	Total Vehicle Weight (Kg)	25000	25000
	Outline Dimension(L × B × H) (mm)	8555 × 2490 × 3800	8715 × 2496 × 3800
	Wheelbase (mm)	3225+1350	3225+1350
	Front Overhang (mm)	1562	1500
	Rear Overhang (mm)	2419	2615

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Website: www.shlongji.com Wheel Loader, Road Roller, Dump Truck

	Min. Clearance Above Ground (mm)	297	314
	Max. Traveling Speed (km/h)	75	90
	Min. Turning Diameter (M)	17.3	17.3
	Oil Consumption per 100 km (under limited conditions)	≤25	≤25
Vehicle Configuration	Clutch	Dry Single Disc Clutch (φ430)	Dry Single Disc Clutch (φ430)
	Gear Box	SINOTRUCK HW18709	SINOTRUCK HW18709
	Driving Type	6 × 4	6 × 4
	Steering Mechanism	ZF8098	ZF8098
	Service Brake	Dual-circuit Air Brake	Dual-circuit Air Brake
	Parking Braking	Spring-powered Air-cut-off Brake	Spring-powered Air-cut-off Brake
	Auxiliary Brake	Engine Exhaust Brake	Engine Exhaust Brake
	Tyre	12.00(R)-20	12.00(R)-20
Engine Parameters	Model	WD615.95(E);WD615.96(E)	WD615.95(E);WD615.96(E)
	Type	In-line 6-cylinder, Water-cooled, Supercharged, Inter-cooled, Electric (Direct) Injection Diesel Engine	In-line 6-cylinder, Water-cooled, Supercharged, Inter-cooled, Electric (Direct) Injection Diesel Engine
	Emission Standard	Euro III	Euro III
	Discharge Capacity (L)	9.726L	9.726L
	Power (KW)	290HP, 336 HP(2200r/min)	290HP, 336 HP(2200r/min)
	Max Torque	1350 N.m(1100-1600r/min)	1350 N.m(1100-1600r/min)
Mixing Drum Parameters	Geometric Volume of Mixing Drum (m ³)	12.8	12.8
	Max Mixing Cubage (m ³)	8-8.8	8-8.8
	Feeding Speed (m ³)	≥3	≥3
	Discharging Speed (≥m ³)	≥1.5	≥1.5
	Leftover Rate	≤0.5%	≤0.5%
	Max Rotating Speed (r/min)	14-16	14-16
	Mixing Drum Obliquity (°)	15	15
	Max Mixing Drum Diameter (mm)	φ2162	φ2162

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xijian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Website: www.shlongji.com Wheel Loader,Road Roller,Dump Truck

Driving System	Speed Reducer	Italian BONFILI-577L	Italian BONFILI-577L
	Hydraulic Pump	US EATON5423-518	US EATON5423-518
	Hydraulic Motor	US EATON4633-045	US EATON4633-045
Water Supply System	Radiator	German AKG with Vacuum Meter	German AKG with Vacuum Meter
	Water Tank Capacity (L)	260	260
	Water Supply Mode	Water Pump; Pneumatic Pump	Water Pump; Pneumatic Pump

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Website: www.shlongji.com Wheel Loader,Road Roller,Dump Truck