



Model		ZZ5256GJBM3846C (9290) HDT5258GJB (9336)	ZZ5257GJBM3847C (9290) HDT5259GJB (9336)
Whole Vehicle Performance & Parameters	Chassis	STEYR King	HOWO
	Curb Weight (Kg)	13000	13220
	Total Vehicle Weight (Kg)	25000	25000
	Outline Dimension(L×B×H) (mm)	9200×2490×3800	9054×2496×3750
	Wheelbase (mm)	3800+1350	3825+1350
	Front Overhang (mm)	1560	1500
	Rear Overhang (mm)	2450	2375

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Website: www.shlongji.com Wheel Loader, Road Roller, Dump Truck

	Min. Clearance Above Ground (mm)	314	314
	Max. Traveling Speed (km/h)	75	90
	Min. Turning Diameter (M)	19.6	19.3
Vehicle Configuration	Oil Consumption per 100 km (under limited conditions)	≤25	≤25
	Clutch	Dry Single Disc Clutch (φ430)	Dry Single Disc Clutch (φ430)
	Gear Box	SINOTRUCK HW18709	SINOTRUCK HW18709
	Driving Type	6×4	6×4
	Steering Mechanism	ZF8098	ZF8098
	Service Brake	Dual-circuit Air Brake	Dual-circuit Air Brake
	Parking Braking	Spring-powered Air-cut-off Brake	Spring-powered Air-cut-off Brake
	Auxiliary Brake	Engine Exhaust Brake	Engine Exhaust Brake
	Tyre	12.00(R)-20	12.00(R)-20
Engine Parameters	Model	WD615.95(E)	WD615.95(E)
	Type	In-line 6-cylinder, Water-cooled, Supercharged, Inter-cooled, Electric (Direct) Injection Diesel Engine	In-line 6-cylinder, Water-cooled, Supercharged, Inter-cooled, Electric (Direct) Injection Diesel Engine
	Emission Standard	China III, Euro III	China III, Euro III
	Max Power (KW)	290HP, 336 HP(2200r/min)	290HP, 336 HP(2200r/min)
	Max Torque	1350 N.m	1350 N.m
Mixing Drum Parameters	Geometric Volume of Mixing Drum (m ³)	14.7	14.7
	Max Mixing Cubage (m ³)	9-10	9-10
	Feeding Speed (m ³)	≥3.5	≥3.5
	Discharging Speed (≥m ³)	≥1.5	≥1.5
	Leftover Rate	Nearly Zero	Nearly Zero
	Max Rotating Speed	14-16	14-16

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Website: www.shlongji.com Wheel Loader,Road Roller,Dump Truck

	(r/min)		
	Mixing Drum Obliquity (°)	13.5	13.5
	Max Mixing Drum Diameter (mm)	φ2162	φ2162
Driving System	Speed Reducer	Italian BONFILI-577L	Italian BONFILI-577L
	Hydraulic Pump Hydraulic Motor	US EATON5423-518 US EATON5433-138	US EATON5423-518 US EATON5433-138
	Radiator	German AKG with Vacuum Meter	German AKG with Vacuum Meter
Water Supply System	Water Tank Capacity (L)	260	260
	Water Supply Mode	Water Pump; Pneumatic Pump	Water Pump; Pneumatic Pump

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Website: www.shlongji.com Wheel Loader, Road Roller, Dump Truck