

XCMG QY25K-II Truck Crane



Dimension	Unit	QY25K-II
Overall length	mm	12650
Overall width	mm	2500
Overall height	mm	3380
Weight		
Total weight in travel	kg	29400
Front axle load	kg	6200
Rear axle load	kg	23200
Power		
Engine model		SC8DK280Q3 / WD615.329(domestic III)
Engine rated power	kW/(r/min)	206/2200 213/2200
Engine rated torque	N.m/(r/min)	1112/1400 1160/1400

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Travel		
Max. travel speed	km/h	75
Min. turning diameter	m	21.5
Min. ground clearance	mm	275
Approach angle	°	16
Departure angle	°	13
Max. grade ability	%	30
Fuel consumption for 100km	L	≈37
Main performance		
Max. rated total lifting capacity	t	25
Min. rated working radius	mm	3000
Turning radius at turntable tail	m	3.065
Max. lifting torque	kN.m	1010
Base boom	m	10.7
Fully extended boom	m	34.19
Fully extended boom+jib	m	42.15
Longitudinal outrigger span	m	5.14
Lateral outrigger span	m	6
Working speed		
Boom luffing time	s	75
Boom full extension time	s	100
Max. swing speed	r/min	≥2.5
Max. speed of main winch (single rope)	m/min	≥120
Max. speed of aux. winch (single rope)	m/min	≥120

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572