

XCMG XS222J Single Drum Vibratory Roller



Item	Unit	XS222J
Operating weight	kg	20000
Weight on front drum	kg	10000
Static linear load	N/cm	516
Speed range	km/h	
Speed I		2.63
Speed II		5.3
Speed III		8.6
Theoretical gradeability	%	30
Min. external turning radius	mm	6500
Steering angle	°	±33
Oscillating angle	°	±10

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China
Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Vibration frequency (high/low)	Hz	33/28
Nominal amplitude (high/low)	mm	1.86/0.93
Excitation force (high/low amplitude)	kN	374/290
Drum diameter	mm	1600
Drum width	mm	2130
Engine model		SC8D185G2B1
Rated power @2000 r/min	kW	136
Engine oil consumption	g/kW.h	223
Hydraulic oil tank capacity	L	170
Fuel tank capacity	L	240

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China
Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572