

XCMG GR 135 Motor Grader



Basic specification	
Engine model	6BT5.9
Rated power/speed	100/2200kw/rpm
Dimension(LxWxH)	8015×2380×3050mm
Operating weight(Standard)	11000kg
Performance specification	
Travelling speed ,forward	5、 8、 13、 20、 30、 42km/h
Travelling speed ,reverse	5、 13、 30km/h
Tractive force(f=0.75)	61.3KN
Max. gradeability	20%
Tire inflation pressure	300kPa
Working hydraulic pressure	16MPa
Transmission pressure	1.3~1.8MPa

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China
Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Operating specification	
Max. steering angle of front wheels	±49°
Max. lean angle of front wheels	±17°
Max. oscillation angle of front axle	±15°
Max. oscillation angle of balance box	16
Frame articulation angle	±27°
Min. turning radius using articulation	6.6m
Blade	
Maximum lift above ground	410mm
Maximum depth of cutting	535mm
Maximum blade position angle	90°
Blade cutting angle	28°—70°
Circle reversing rotation	360°
Moldboard width X height	3710×610mm

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China
Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572