

XCMG XE215LL Excavator



Model		Unit	XE215CLL
Operating weight		kg	22350
Standard bucket capacity		m ³	0.5
Engine	Engine Model	/	ISUZU BB-6BG1TRP
	Direct injection	/	√
	Four strokes	/	√
	Water cooling	/	√
	Turbo charged	/	√
	Air to air intercooler	/	×
	No. of cylinders	/	6
	Rated power/speed	kw/rpm	106.5/1950

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

	Max. torque/speed	N.m	551/1600
	Displacement	L	6.494
The main performance	Travel speed	km/h	5.5/2.8
	Swing speed	r/min	12.2
	Max. gradeability	/	≤35
	Ground pressure	kPa	36.2
	Max.Bucket digging force	kN	78.7
	Max.arm crowd force	kN	40
	Max.traction force	kN	179
Hydraulic system	Main pump	/	2 Plunger pump
	Rate flow of main pump	L/min	2×206
	Max pressure of prime relief valve	MPa	32.3/34.3
	Max pressure of travel system	MPa	34.3
	Max pressure of swing system	MPa	28
	Max pressure of pilot system	MPa	3.9
Oil capacity	Fuel tank capacity	L	360
	Hydraulic tank capacity	L	220
	Engine lubrication	L	25
Overall dimensions	A Overall length	mm	12050
	B Overall width	mm	3190
	C Overall height	mm	3150
	D Overall width of upperstructure	mm	2710
	E Track length	mm	4255
	F Overall width of undercarriage	mm	3190
	G Crawler width	mm	800
	H Track length on ground	mm	3462
	I Crawler gauge	mm	2390

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

	J Clearance under counter weight	mm	1060
	K Ground clearance	mm	470
	L Min.tail swing radius	mm	2750
Working range	A Max. digging height	mm	13250
	B Max. dumping height	mm	10942
	C Max. digging depth	mm	11690
	D 8inch horizontal digging depth	mm	---
	E Max. vertical wall digging depth	mm	11200
	F Max. digging reach	mm	15394
	G Min. swing radius	mm	4835
	Angle of arm deflection	Degree	

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572