

## XCMG XE235C Excavator



Model	Unit	XE230C
Operating weight	kg	23500
Standard bucket capacity	m <sup>3</sup>	0.9~1.1
Engine	Engine Model	/ ISUZU CC-6BG1TRP
	Direct injection	/ √
	Four strokes	/ √
	Water cooling	/ √
	Turbo charged	/ √
	Air to air intercooler	/ √
	No. of cylinders	/ 6
	Rated power/speed	kw/rpm 128.5/2100

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China  
Post Code: 201100

Website: [www.shlongji.com](http://www.shlongji.com)

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572

	Max. torque/speed	N.m	637/1800
	Displacement	L	6.494
The main performance	Travel speed	km/h	5.5/3.5
	Swing speed	r/min	12.1
	Max. gradeability	/	≤35
	Ground pressure	kPa	51.7
	Max.Bucket digging force	kN	163
	Max.arm crowd force	kN	116
	Max.traction force	kN	194.8
Hydraulic system	Main pump	/	2 Plunger pump
	Rate flow of main pump	L/min	2×231
	Max pressure of prime relief valve	MPa	31.5/34.3
	Max pressure of travel system	MPa	34.3
	Max pressure of swing system	MPa	23
	Max pressure of pilot system	MPa	3.9
Oil capacity	Fuel tank capacity	L	400
	Hydraulic tank capacity	L	240
	Engine lubrication	L	25
Overall dimensions	A Overall length	mm	10160
	B Overall width	mm	2990
	C Overall height	mm	3100
	D Overall width of upperstructure	mm	2830
	E Track length	mm	4270
	F Overall width of undercarriage	mm	2990
	G Crawler width	mm	600
	H Track length on ground	mm	3462
	I Crawler gauge	mm	2390

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China  
Post Code: 201100

Website: [www.shlongji.com](http://www.shlongji.com)

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572

	J Clearance under counter weight	mm	1050
	K Ground clearance	mm	470
	L Min.tail swing radius	mm	2985
Working range	A Max. digging height	mm	9595
	B Max. dumping height	mm	6725
	C Max. digging depth	mm	6960
	D 8inch horizontal digging depth	mm	6750
	E Max. vertical wall digging depth	mm	6090
	F Max. digging reach	mm	10240
	G Min. swing radius	mm	3850
	Angle of arm deflection	Degree	

---

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China  
Post Code: 201100

Website: [www.shlongji.com](http://www.shlongji.com)

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572