

XCMG RP1356 Road Paver



Items	Unit	Parameters	
		DV25Q-I	E600DV
Paving width	m	2.5 ~ 12 (Option: 14m)	3 ~ 9
Max. paving thickness	mm	350	350
Paving speed	m/min	0 ~ 18	0 ~ 18
Travel speed	km/h	0 ~ 3.6	0 ~ 3.6
Hopper capacity	t	14	14
Centre crown ratio	%	-1 ~ 4	-1 ~ 3
Double vibrator speed	r/min	0 ~ 1470	0 ~ 1470
Vibration frequency	Hz	0 ~ 42	0 ~ 50
Engine		TCD2013L062V Deutz	TCD2013L062V Deutz

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Rated power/speed	kW	182	182
Compactness	%	≥90	≥90
Evenness	mm/3 m	≤2	≤2
Theoretical productivity	t/h	800	700
Dimension	mm	6402×2656×3880	6980×3000×3880
Machine weight	t	22.2 ~ 31.2	24 ~ 26.5
Paver		RP1356	
Screed Model		DV25Q-I	E600DV
Type	/	Double vibrator, eccentric vibration, gas heating	Double vibrator, eccentric vibration, electrical heating
Extension type	/	Mechanical assembly	Hydraulic extension
Width	m	2.5 ~ 12 (Option: 14m)	3 ~ 9
Vibrating speed	r/min	0 ~ 1470	0 ~ 1470
Main amplitude of vibrator	mm	3、5、7、9	5
Auxiliary amplitude of vibrator	mm	0、3、6、9、12	0、5、10
Vibration frequency	Hz	0~42	0~50
Extra-long screed	mm	1500×4、1000×2、500×2、250×2	750×4

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China
Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572