

XCMG RP451L Road Paver



Items	Unit	Parameters
Basic paving width	m	2
Max. paving width	m	4.5
Max. paving thickness	mm	150
Paving speed	m/min	0~13
Travel speed	km/h	0~13
Theoretical Productivity	t/h	240
Hopper Capacity	t	12
Gradeability	%	20
Pavement evenness	mm/3m	3
Transverse levelling accuracy	%	±0.03
Centre crown ratio	%	0~+3
Engine model		4JR3G1
Engine power	kw	55
Engine speed	r/min	2200

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Fuel tank capacity	L	130
Machine weight	t	10.5
Dimension	mm	5690X2070X3590
Auger speed	r/min	0~73
Conveyor speed	m/min	0~30
Vibration frequency	Hz	3~42
Screed heating		Gas heating
Auger and conveyor control		Automatic Control by Ultrasonic Sensors
Automatic levelling control		Simulation Control Simulation control

Items	Unit	Parameters
Screed model	/	EV35Q
Type	/	Gas heating, vibration
Extension	/	Hydraulic
Width	m	2.0-4.5
Vibrator speed	Hz	0-42

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572