

XCMG RP601J-RP701J Road Paver



Items	Unit	Parameters
Basic paving width	m	2.5
Max. paving width	m	6/7
Max. paving thickness	mm	300
Paving speed	m/min	2.0~5.98
Travel speed	km/h	1.52~4.55
Theoretical Productivity	t/h	400
Hopper Capacity	t	13
Gradeability	%	20
Pavement evenness	mm/3m	3(Asphalt)/5(Stabilized soil)
Transverse levelling accuracy	%	0.02
Engine model	/	YC6108G
Engine Parameters	kW/rpm	92/2300

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Fuel tank capacity	L	160
Machine weight	t	19.3
Dimension	mm	6636×2580(3000)×3680

Items	Unit	Parameters	
Screed model	/	475Q	TVC
Type	/	Single vibrator+Gas heating	Single vibrator+Gas heating
Extension	/	Hydraulic	Mechanical assembly
Width	m	2.5~6/7	3~6/7
Vibrator speed	r/min	0~1500	0~1500
Vibrator amplitude	mm	4	4
Extra-long screed	mm	625/1125	750、500、250

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572