

XCMG RP601L-RP701L Road Paver



Items	Unit	Parameters
Basic paving width	m	2.5
Max. paving width	m	6.0/7.0
Max. paving thickness	mm	300
Paving speed	m/min	0~18
Travel speed	km/h	0~18
Theoretical Productivity	t/h	400
Hopper Capacity	t	13
Gradeability	%	20
Pavement evenness	mm/3m	3
Transverse levelling accuracy	%	±0.03
Centre crown ratio	%	0~+3
Engine model		D4114ZG2B

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Engine power	kw	100
Engine speed	r/min	2400
Fuel tank capacity	L	170
Machine weight	t	15.3~19
Dimension	mm	6096X2580X3832
Auger speed	r/min	0~82
Conveyor speed	m/min	0~36
Vibrator speed	r/min	0~1470
Vibrator amplitude	mm	4
Screed heating		Electrical heating
Auger and conveyor control		Automatic Control by Ultrasonic Sensors
Automatic levelling control		Simulation control

Items	Unit	Parameters
Screed model	/	475
Type	/	Gas heating, vibration
Extension	/	Hydraulic
Width	m	2.5-6.0/7.0m
Vibrator speed	rpm	0-1470

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572