

## XCMG G14SQ Concrete Truck Mixer



Type	Model	Unit	G14SQ
Performance of mixing drum	Geometric volume	m <sup>3</sup>	22.5
	Mixing volume	m <sup>3</sup>	14
	Maximum diameter of drum body	mm	2432
	Length of mixing drum	mm	6748
	Angle of inclination	°	10
	Rotating speed	r/min	0~14
	Charge speed	m <sup>3</sup> /min	≥3
	Discharge speed	m <sup>3</sup> /min	≥2

---

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: [www.shlongji.com](http://www.shlongji.com)

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572

	Residue ratio of discharge	%	<0.7
	Range of slump	cm	5~21
Hydraulic system	Oil pump		international brand
	Motor		international brand
	Reduction gears		international brand
	Hydraulic circuit		Closed type
Water supply	water tank capacity	L	450
	Way of water supply		Pneumatic
Complete machine	Brand of chassis		C&C Trucks
	Chassis model		SQR3250D6T4-E
	Type of driving		Left-hand drive
	Curb weight	kg	17200
	maximum gross weight	kg	25000
	Type of drive		8×4
	Wheel base	mm	4200+1350
	Tyre		12.00R20
	Means of power takeoff		Power takeoff by flywheel
	Notice model		
	External dimensions	(length×width×height)m m	10350×2500×3995
Engine	Model		YC6K1034-30
	Rated power	Kw/r/min	250
	Displacement	L	10.338
	Emission standard		GB III

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: [www.shlongji.com](http://www.shlongji.com)

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572