

## XCMG XGC 130 Crawler Crane



Items	Unit	Data
Basic boom	T	135
Fixed jib	T	20
Max. load moment	t/m	722
Boom length	M	16-76
Boom working condition	°	30-80
Fixed jib working condition	°	30-80
Fixed jib length	M	13-31
Winch mechanism max single line speed(no load, at 5th layer)	m/min	120

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: [www.shlongji.com](http://www.shlongji.com)

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Boom elevating mechanism max. single line speed(no load, at 3rd layer)	m/min	2×45
Max slewing speed	r/min	1.5
Max traveling speed	Km/h	1.3
Grade ability	%	30
Average ground pressure	Mpa	0.089
Engine power	Kw	206
Mass of the vehicle as a whole( including main hook block and 16m boom)	T	122
Max mass of single unit in travel configuration	T	37
Max dimension of single unit in travel configuration(L×W×H)	m	11.0×3.0×3.3

---

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: [www.shlongji.com](http://www.shlongji.com)

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572