Shantui SD22C Bulldozer



ITEM	UNIT	SD22C
L×W×H		
(Ripper not included)	mm	5750×4200×3395
Operating weight		
(Ripper not included)	t	24.6
		Cummins
Engine	-	NT855-C280S10
Rated power	kW/rpm	162/1800
Gradeability	0	30
Blade type	-	Coal blade
Blade width	mm	4200×1350
Dozing capacity	m ³	9

Shanghai Longji Construction Machinery Co., Ltd.Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, ChinaPost Code: 201100Website: www.shlongji.comE-mail: info@shlongji.comFax: +86-21-541-71572

ongji Construction.	Machinery	上海龙基工程机械有限公司
Ma $ imes$ drop below ground of blade	mm	540
Lift height of blade	mm	1210
Ripper type	-	Single ripper Three-shank ripper
Ripping depth of ripper	mm	Single ripper 695 Three-shank ripper 666
Lifting height of ripper	mm	Single ripper515 Three-shank ripper 555
Number of carriers (each side)	-	2
Number of track rollers (each side)	-	6
Number of track shoes (each side)	-	38
Width of track shoe	mm	660
Track gauge	mm	2000
Ground length and ground pressure	mm/MPa	2730-0.066
Pitch	mm	216
	km/h	0 - 3.6
Forward speed		0 - 6.5
		0 - 11.2
Reverse speed		0 - 4.3
	km/h	0 - 7.7
		0 - 13.2

Shanghai Longji Construction Machinery Co., Ltd.Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, ChinaPost Code: 201100Website: www.shlongji.comTel: +86-21-541-71571E-mail: info@shlongji.comFax: +86-21-541-71572

Longji Construction Machinery

The SD22C coal bulldozer is a modified form of the SD22, featuring advanced performance, high reliability, low fuel consumption and convenient maintenance. The SD22C has a high-capacity coal-dozing blade, and is equipped with an engine intake pre-filtering device, helping adapt it to transferring, paving and stacking operations often performed in coal mines and electricity coal yards.