

Shantui SD32W Bulldozer



ITEM	UNIT	SD32W
L×W×H (Ripper not included)	mm	6880×4130×2725
Operating weight (Ripper not included)	t	38
Engine	-	CumminsNTA855-C360S10
Rated power	kW/rpm	235/2000
Gradeability	°	30
Blade type	-	Straight tilt blade
Blade width	mm	4130×1590
Dozing capacity	m ³	10
Ma× drop below ground of blade	mm	560
Lift height of blade	mm	1560
Ripper type	-	Single ripperThree-shank ripper
Ripping depth of ripper	mm	Single ripper 1250Three-shank ripper 842

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Lifting height of ripper	mm	Single ripper 955Three-shank ripper 883
Number of carriers (each side)	-	2
Number of track rollers (each side)	-	7
Number of track shoes (each side)	-	41
Width of track shoe	mm	560
Track gauge	mm	2140
Ground length and ground pressure	mm/MPa	3150-0.105
Pitch	mm	228.6
Forward speed	km/h	0 - 3.6
		0 - 6.6
		0 - 11.5
Reverse speed	km/h	0 - 4.4
		0 - 7.8
		0 - 13.5

Based on the SD32, the SD32W rock bulldozer is specially designed for operation in tough working conditions with hard rock and frozen earth. The SD32W is equipped with a hydraulic drive system with hydraulic control technology, and an advanced structure, providing reliable performance and convenient and flexible operation. It also has a rock-type track and blade, allowing the SD32W to adapt to the heavy condition necessary when working with hard rock and frozen earth.

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572